

Milwaukee 2854-22R

M18 FUEL™ 3/8" Compact Impact Wrench w/ Friction

Ring Kit

Item Number: MI-285422R



Our M18 FUELTM 3/8" Compact Impact Wrench w/ Friction Ring is the most compact in its class, delivering you the most access in tight spaces, up to 250 ft-lbs of nut-busting torque, and maximum workspace visibility. This battery-powered impact wrench measures only 4.8" in length with a POWERSTATETM Brushless motor to provide the power to remove stubborn fasteners, even in confined spaces. The MILWAUKEE® 3/8" Compact Impact Wrench has tri-LEDs that surround the anvil to deliver you brighter light with fewer shadows. 4-Mode DRIVE CONTROLTM offers greater precision with a range of pre-set RPM and IPM levels, selectable from a single button on the tool. By selecting Mode 4, AUTO SHUT-OFFTM control applies no more than 20 ft-lbs of torque for hand-tight fastening applications to prevent overtightening. Mode 4 also features Bolt Removal Control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops. REDLINK PLUSTM Intelligence electronics make these controls possible while ensuring maximum performance, protecting the tool against overloads, over-heating, and over-discharge. The M18TM REDLITHIUMTM battery pack (not included) fits M18TM tools, delivering more work per charge and more work over the life of the pack.



Features

- Friction ring (hog ring) ensures quick and easy socket changes
- Compact length provides most access in tight spaces
- Powerstate[™] brushless motor
- Tri-LEDs deliver high definition lighting to increase workspace visibility with less shadows
- 4-mode Drive Control[™] provides greater control over output speed and power
- Auto Shut-Off[™] control applies no more than 20 ft-lbs of torque for hand-tight fastening applications to prevent over-tightening
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops
- Redlink Plus[™] Intelligence ensures maximum performance and protects from overloads, heating and over-discharge
- Works in up to 69kV environments
- Compatible with all M18[™] batteries & chargers

Specifications

Fastening Torque	250 ft/lbs
Nut-Busting Torque	250 ft/lbs
IPM	0 - 3,500
RPM	0 - 2,400
Weight (LBS)	3.9
Warranty	5 Years
Battery Warranty	2 Years