

## L.B. White Premier 80DF

### Dual Fuel Heater, Direct-Fired, 80,000 BTU/Hr

Item Number: LB-PREMIER80DF



L.B. White's Premier series of enclosed flame, ductable, direct-fired heaters are perfect for small, hard to reach areas, as well as large construction applications. Premier heaters produce extremely clean, dry heat despite being a direct-fired heater. Although fresh air ventilation is required, these heaters are effectively used for "dry heat" applications such as drywalling with excellent results. All units are shipped ready-to-use and are extremely easy to operate. The compact thermostat provides easy, effective temperature management and the onboard diagnostics make maintenance a breeze.

### Features

- Quickly switch between propane (LP) and natural gas (NG)
- Enclosed-flame design promotes safer work environments and adds the ability to duct
- 99% direct-fired fuel efficiency
- Optional "fan-only" mode
- Very quiet while operating
- Fits through standard 36" door frame
- Dependable electronic ignition

- Status lights indicate heating mode stage and quickly aid diagnosis of common issues when troubleshooting
- Tri-Shield steel case
- Gas hose, regulator, and thermostat included
- Certified to ANSI and CSA standards for safety and rated for indoor-outdoor use
- Ducting and diffusers available

## Specifications

|                             |                                   |
|-----------------------------|-----------------------------------|
| <b>Fuel Source</b>          | Dual Fuel (LP/NG)                 |
| <b>Heat Output (BTU/Hr)</b> | 80,000                            |
| <b>Airflow (CFM)</b>        | 450 CFM                           |
| <b>Max Fuel Consumption</b> | LP: 3.7 lbs/hr<br>NG: 80 cu ft/hr |
| <b>Amperage (A)</b>         | Starting: 5.0 A<br>Running: 1.5 A |
| <b>Horsepower</b>           | 1/8 HP                            |
| <b>Sound (Decibels)</b>     | 70                                |
| <b>Duct Size</b>            | 12"                               |
| <b>Max Duct Length</b>      | 12-ft                             |
| <b>Dimensions</b>           | 28" x 13.5" x 22"                 |
| <b>Weight (LBS)</b>         | 79 LBS                            |
| <b>Certification</b>        | CSA                               |
| <b>Warranty</b>             | 2 Years                           |