

Patron D-160

LGR Dehumidifier, 160 PPD

Item Number: PA-D160



The Patron D-160 dehumidifier is a portable industrial-grade unit equipped with advanced "LGR" (Low Grain Refrigerant) technology, engineered to tackle high humidity levels in various industrial environments. It efficiently extracts excess moisture from the air, making it ideal for remediation projects, construction sites, or any space requiring effective humidity control. Its user-friendly control panel and portable design allows for versatile deployment wherever moisture management is essential.

Features

- LGR refrigerant provides enhanced, deeper drying at lower temperatures and humidities
- · Folding handle allows for stackability
- Digital control panel with humidistat, hour meter, timer, and humidity controls
- · Quick-connect drain hose
- Removeable panel for easy pump access
- Rugged 12" semi-pneumatic wheels
- Rotomolded body for maximum durability



- Hot gas valve for quick defrost
- High-performance pleated filter protects the unit while improving air quality

Specifications

| Water Removal @ 80°, 60% RH | 93 pints/day |
|-----------------------------|-----------------------------|
| Water Removal @ 86°, 80% RH | 160 pints/day |
| Water Removal @ Saturation | 190 pints/day |
| Operating Temperature | 33°F - 100°F |
| Inlet Filter | Pleated MERV 10 PA-D7000 |
| Airflow (CFM) | 386 |
| Voltage (V) | 115 V |
| Refrigerant | R32 |
| Wattage (W) | 835 W |
| Amperage (A) | 8 A |
| Drain Hose | 20 ft |
| Cord Length | 26 ft |
| Certification | cETLus |
| Dimensions | 20" x 19" x 32" |
| Weight (LBS) | 97 |
| Warranty | 1 Year |