

Milwaukee 2967-22

M18 FUEL™ High Torque ½" Impact Wrench Kit

Item Number: MI-296722



Our M18 FUELTM ½" High Torque Impact Wrench w/ Friction Ring is the most power-dense impact wrench in its class, provides greater access in tight spaces, and maximizes productivity through faster removal speeds. The POWERSTATETM Brushless Motor delivers up to 1,200 ft-lbs of Fastening Torque and 1,600 ft-lbs of Nut-Busting Torque when paired with our M18TM REDLITHIUMTM FORGETM Batteries, while the compact size at 7.6" in length gives users greater access in tight spaces. The M18 FUELTM ½" High Torque Impact Wrench w/ Friction Ring maximizes productivity on the jobsite and in the shop by removing stubborn bolts and fasteners faster than cordless competitors. Our patented battery isolation system provides a secure battery connection and controls vibration transmitted to the pack. Tri-LEDs surround the anvil to deliver brighter light with fewer shadows. 4-Mode DRIVE CONTROLTM offers greater precision with a range of pre-set RPM and IPM levels, selectable from a single button on the tool. By selecting Mode 4, AUTO SHUT-OFFTM control applies no more than 50 ft-lbs of torque for hand-tight fastening applications to prevent overtightening. Mode 4 also features Bolt Removal Control that delivers our users full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops. The ½" Friction Ring design allows for quick & tool-free socket changes.



Features

- Most Power Dense Best Combination of Power and Size
- POWERSTATE™ Brushless Motor delivers up to 1,200 ft-lbs of Fastening Torque & 1,600 ft-lbs of Nut-Busting Torque w/ M18™ REDLITHIUM™ FORGE™ Battery
- Up to 2" Shorter Length. 7.6" in length provides most access in tight spaces
- Fastest Removal Speeds. Maximize productivity on the jobsite and in the shop
- Patented battery isolation system ensures a secure battery connection and controls vibration transmitted to the pack
- Tri-LEDs deliver high definition lighting to increase workspace visibility with less shadows
- 4-Mode DRIVE CONTROL™ provides greater control over output speed and power. Includes auto shut-off and bolt-removal mode
- Bolt removal mode provides maximum nut-busting torque to break fastener free, then slows to 750 RPM for more control when removing fasteners
- AUTO-SHUTOFF[™] control prevents over tightening and increases productivity by applying no more than 50 ft-lbs of torque
- Mode 1 IPMs: 0 1,300; Mode 2 IPMs: 0 2,200; Mode 3 IPMs: 0 2,400; Mode 4 IPMs: 0 2,400
- Mode 1 RPMs: 0 700; Mode 2 RPMs: 0 1,300; Mode 3 RPMs: 0 2,000; Mode 4 RPMs: FWD: 0 - 900, REV: 0 - 2,000 / 0 - 750
- · Friction ring (hog ring) ensures quick and easy socket changes
- REDLITHIUM™ batteries deliver more work per charge and more work over the life of the battery
- REDLINK PLUS[™] Intelligence ensures maximum performance and protects from overloads, heating and over-discharge
- Compatible with all M18[™] batteries & chargers

Specifications

Weight (LBS)	7.5
Fastening Torque	1100 ft-lbs
Nut-Busting Torque	1500 ft-lbs
IPM	0 - 2,400 IPM
RPM	0 - 2,000
Warranty	5 Years